

Venkata Narayana Active Ingredients Private Limited

(Formerly Nutra Specialities Private Limited)

Ref: VNAI/MoEF & CC-RO/ECCR/JUNE/2020

June 22, 2020

To

The Director

Ministry of Environment, Forest and Climate Change (MoEF &CC) Regional Office (SEZ), 1st & 2nd Floor, Handloom Export Promotion Council, 34, Cathedral Garden Road, Nungambakkam,

Chennai-34

Respected Sir,

<u>Sub:</u> M/s Venkata Narayana Active Ingredients Private Limited (Formerly M/s Nutra Specialties Private Limited) located at Sy.No:69, Chandrapadiya Village, Vinjamur Mandal, SPSR Nellore District, Andhra Pradesh submitting EC half yearly compliance report for the month of June-2020- Regarding.

Ref: EC order F.No. J-11011/1313/2007-IA(II)(I) Dated 2nd February 2009

This has reference cited above on the aforementioned subjected, we are herewith enclosing Half yearly (June-2020) condition wise compliance report of Environmental Clearance for Part-A Specific conditions and Part-B General conditions of our Active Pharmaceutical Ingredients (APIs) manufacturing unit located at Sy.No:69, Chandrapadiya Village, Vinjamur Mandal, SPSR Nellore District, Andhra Pradesh for your kind perusal and consideration.

Kindly acknowledge the receipt of the same.

Thanking you,

For M/s Venkata Narayana Active Ingredients Private Limited.

Yours Faithfully,

(Authorized Signatory)

Encl: EC condition wise compliance report with Annexure-I to Annexure-VI.

Regd. Office: Venkata Narayana Towers, 3rd Floor, New No.60, Old No.35, Venkatanarayana Road, T.Nagar, Chennai - 600017. Tamil Nadu. Phone: +91-44-42984141.

Factory: Sy. No.69, Chandrapadiya Village, Vinjamur Mandal, S.P.S.R. Nellore District - 524 228. Andhra Pradesh, Phone: +91-8627-300100

Web: www.vnai.in / CIN: U24231TN2005PTC057504

VENKATA NARAYANA ACTIVE INGREDIENTS PRIVATE LIMITED (Formerly Nutra Specialties Private Limited) Sy.No:69, Chandrapadiya (V),Vinjamur(M),SPSR Nellore District,Andhra Pradesh.

CONDITION-WISE COMPLIANCE REPORT OF ENVIRONMENTAL CLEARANCE

Ministry of Environment, Forest & Climate Change, Govt of India EC Order No:F.No.J-11011/1313/2007-IA II (I) Dated February 2, 2009

Date of submission: 22.06,2020

S.No	Conditions of Environmental Clearance	Status of Compliance
A.SPE	CIAL CONDITIONS	1
	The company shall implement Good Laboratory Practices (GLP)	Complied We have established good laboratory facilities for analysing the quality of the products and also monitoring the Chemical Oxygen Demand, Dissolved oxygen, Biological Oxygen Demand, TDS and pH from effluent water. The laboratory is equipped with the following I. High performance liquid chromatography (HPLC) II. Gas Chromatography (GC) III. Infrared spectroscopy IV. Ultraviolet spectroscopy V. Total organic compound analyser VI. Particle size analyser VII. Conductivity meter IX. Polari meter However, the Environmental parameters such as Ambient Air Quality, Ambient Noise levels and Stack emissions are monitored through MoEF&CC authorised third party laboratory. Laboratory facility photo is attached as Annexure-I
Ð	The gaseous emissions (HBr,SOx,NOx & HCI) particulate matter from various process units shall conform to the standards prescribed by the concerned authorities from time to time. At no time,the emission levels shall go beyond the stipulated standards. In the event of failure of pollution	There are three sources of gaseous emissions (Two boiler (2x4 TPH). Two

control system(s) adopted by the unit, the respective unit shall DG sets (1x500 KVA & 1X 725 KVA. not be restarted until the control measures are rectified to achieve the desired efficiency

and other process emissions). Bio briquettes is used as the fuel for boiler

For boiler, cyclone separator followed by bag filleter is provided to control SPM emissions. Adequate stack height with acoustic enclosures is provided for DG sets. Two sage scrubbers (2 Nos) are provided for process emissions.

Monitoring of gaseous emissions and particulate matter from various process units was carried out on quarterly basis through MoEF&CC recognized third party laboratory. The monitored data shows the that the values are within standards.

In addition to this, we have installed 2 nos of Online Ambient Air quality monitoring stations in down wind and upwind directions for monitoring PM10, PM2.5, SO2, NOx. The online real time monitoring data is being transmitted to APPCB/CPCB servers.

Boilers, cyclone separators & DG sets photo is enclosed as Annexure-II

iii Ambient air quality monitoring stations shall be set up in the downwind direction as well as where maximum ground level concentration are anticipated in consultation with the SPCB.

Complied

There are three AAQ monitoring stations has been set up in the downwind direction as well as where maximum level ground concentrations are anticipated in consultation with SPCB and is being monitored on quarterly basis through MoEF & CC approved laboratory for the parameters of PM10, PM2.5, SO2, NOx. The monitored data shows the that the values are within the NAAQ standards.

In addition to this, we have installed 2 nos of Online Ambient Air quality

iv	Process emissions is in the form of HCI,SO2 and HBr shall be scrubbed in the scrubber. The scrubber efficiancy shall be 99%	monitoring stations in downwind and upwind directions for monitoring PM10, PM2.5, SO2, NOx. The online real time monitoring data is being transmitted to APPCB/CPCB servers. Online AAQ photos are enclosed as Annexure-III Complied Process emissions (HCI, SO2 and HBr) are being scrubbed in the two-
		stage scrubber. The scrubber efficiency is about 98% as informed.
V	For control of particulate emissions, boilers shall provided with cyclones separators and stack height as per Central Pollution Control Board guidelines.	Complied We have installed two boilers at the capacity of 2x4 TPH. Cyclone separators are provided for boilers. The boilers are equipped with bag filter with stack height of 30 m height as stipulated by PCB. Scrubbers are also provided in manufacturing blocks. Reactors are equipped with primary and second condensers with chilled brine circulation to control fugitive losses of solvents. Solvents to reactors are transferred through closed pipeline. Reactors are provided with scrubbers as per requirement as informed.
vi	Spent solvents shall be recovered as far as possible & recovery shall not be lessthan 95 percent. During purification process, solvent vapours are emitted from purification tanks as fugitive emissions. Action shall be taken to reduce the emissions as far as possible. All venting equipment shall have vapour recovery system	Plant (SRP) with four columns.

		 b) All distillation units are provided with secondary condensers to trap the uncondensed solvent thereby maximise solvent recovery and minimise fugitive emissions. c) All bulk storage tanks are provided with vent condensing system along with breather valve provision to minimise solvent losses/emissions. SRP photo is enclosed as Annexure-IV
vii	The company shall undertake the following waste minimization measures.	Complied The industry has adopted following waste minimization measures
	A.Metering and control of quantities of active ingredients to minimize waste.	A. All the raw materials taken by metering and weighing.
	B.Re-use of byproducts from the as raw materials or as raw material substitutes in other processess	B. At present no by-products have been produced.
	C.Use of automated filling to minimize spillages	C. Use of automated filling to minimize spillage.
	D.Use of closed feed system into batch reactors	D. Closed feed system for charging of raw materials into reactors
	E.Venting equipment through vapour recovery system	E. Provided double condensers to reactors with RT/Chilled water and brine circulation for vapour recovery system
	F.Use of high pressure hoses for equipment clearing to reduce waste water generation	F. Using pressure hoses for cleaning of equipment to reduce wastewater generation.
viii	Fugitive emissions in the workzone environment, product, raw material storage area shall be regularly monitored. The emissions shall conform to the limits imposed by SPCB.	Complied Monitoring of Fugitive emissions in the work zone environment, product, and raw materials storage area was carried out on quarterly basis through MoEF &CC recognized third party laboratory. The monitored data shows that the values are well within the limits.
ix	The project authorities shall provide the chilled brine sollution in secondary condenser for condensation of the VOCs and	

solvent recovery shall not be	e lessthan 95	solution conden We hav Plant (S are fou used Isoprop	in secondary condenser for sation of the VOCs. we installed Solvent Recovery SRP) with four columns. There is types of major solvents are (Acetone, Ethyl acetate, byl alcohol and omethane) and the recovery is
r monitoring shall be carriedou	ut and reports	one at	Complied are 12 reactors and 12 vents, tached to each reactor. All /vents are connected online ant emission details.
		the Mol	r monitoring is carriedout by EF authorised laboratories and ing reports to the Regional egularly.
olvent loss, following measure	s shall be		Complied
olvent handling pump shall ha			Chilled brine condenser system provided for all the reactors to minimise vapor losses.
to prevent leakages.			Mechanical seals provided to reactor and solvent handling pump to prevent the leakages.
•			Primary and secondary condensers are provided with sufficiant HTA and residance time so as to achieve more
	electrical	D,	recovery. Proper earthing has been
			provided to all equipments and regular inspections are done to maintain continuity
The state of the s	5.010111	E,	Flame proof mechanism has been provided and breather valves installed to solvent storage tanks to prevent lossess.
	nall provide the monitoring edrimonitoring shall be carriedor SPCB, CPCB and Ministry's Respective to the connected to chilled brine of the ch	nall provide the monitoring equipment with remonitoring shall be carriedout and reports SPCB, CPCB and Ministry's Regional Office olivent loss, following measures shall be be connected to chilled brine condenser olivent handling pump shall have a to prevent leakages. The shall be provided with sufficient HTA and to as to achieve more than 95% recovery.	when the provided the monitoring equipment with respect to the provided and monitoring shall be carriedout and reports and monitoring shall be carriedout and reports. There is one at reactor for instance of the provided monitoring powers shall be an accordance of the provided with sufficient HTA and the provided with sufficient HTA and the provided monitoring is done. D. The solvent storage provided with breather valve to prevent the provided with breather valve to prevent the provided with breather valve to prevent the provided is an accordance of the provided with breather valve to prevent the provided is an accordance of the provided with breather valve to prevent the provided is an accordance of the provided in all the electrical ever solvent handling is done. D. The plant is a provided in all the electrical ever solvent handling is done. D. The plant is a provided in all the electrical ever solvent handling is done.

The process emissions VOCs and particulate matter from various units shall conform to the standards prescribed by the concerned authorities from time to time. At no time, the emission levels shall go beyond the stipulated standards. In the event of failure of pollution control system(s) adopted by the unit, the unit shall be immediately put out of operation and shall not be restarted unit until the desired efficiency has

been achieved.

Complied

- We have installed online VOC analyser with data logger and portable VOC analyser. As informed, we are submitting the data on monthly to SPCB.
- 2) The gaseous emissions and particulate matter from various process units is being carried out on quarterly basis through MoEF & CC recognized third party laboratory for the parameters of PM10, PM2.5, SO2, NOx. The monitored data shows the that the values are within the standards prescribed by the concerned authorities. control gaseous emissions following have been adopted
- Installation of two stage scrubbers (2 nos) for the vents of the reactors in which acidic reactions are being carried.
- Installation of dual stage condensers for all the reactors to avoid process emissions.
- Equalization tanks of ETP are being covered with FRP hoods and the vents of the hoods are connected to scrubbers.
- All DG Sets are provided with sufficient stack height as per norms.
- 3) As informed, at no time, the emission levels has gone beyond the stipulated standards and the factory operations are being stopped in the event of failure of pollution control systems

adopted and being re-started only after rectification. Effluent generation shall not exceed 67.03 m³/d. The effluent Complied xiii shall be segregated into high COD and low COD streams. The high COD effluent shall be forced evaporated. The We have installed 100 KLD Effluent effluent with high COD shall be stripped for solvent before Treatment Plant (ETP). sending into the forced evaporator. The condensate from the evaporator and effluent from the utility blow downs shall be The effluent generation is about 45treated in ETP and treated effluent conforming to the 55 KLD which is being sent to ETP for prescribed standards shall be used for green development. treatment. The concentrate from MEE shall be filter press. The salt obtained fromm MEE shall be disposed in to secured land fill (TSDF)after packaging in HDPE bags. The domestic effluent All effluents are being segregated into (6m3/d)shall be sent to septic tank followed by soakpit. HTDS and LTDS. All HTDS effluents are treated through stripper followed by Multi Effect Evaporator (MEE) and agitated Thin Film Dryer (ATFD). The condensate generated from MEE and ATFD are mixed with LTDS effluent and further treated in biological ETP and RO Plant. Salts are being disposed to TSDF for secured land filling. LTDS and all blowdowns subjected to ETP and water is being used for cooling towers/boiler makeup and garden development after confirming the limits prescribed by APPCB. The ETP sludge generated from ETP operations are being sent to TSDF for secured landfill. We have installed online flow meters for HTDS and LTDS and connected to the SPCB/CPCB. ETP. MEE & Flow meters are enclosed as Annexure-V. χiν The company shall develop in water harvesting structures to Complied harvest the run off water for recharge of ground water. We have developed water harvesting structure with the capacity of 500 KL to harvest the run-off water for recharge of ground water.

ΧV	Green belt shall be provideed in an area 33% to mitigate the effects of fugitive emission all around the plant .	Complied
	Development of belt shall be as per the central polluction Control Board guidelines.	Green belt has been developed in an area of more than 33% (13 acers) of the total project area (33% acers) by plating Pongamia, neem, coconut trees, conocorpus etc in consultation with the local DFO and survival of the green belt is good.
		Greenbelt development photographs are enclosed as Annexure-VI
xvi	Permission shall be obtained to draw ground water from the state Ground Water Board/ Central Ground water board as may be applicable to this case.	Complied We have obtained permission from State Ground Water & Water Audit dept, Government of Andhra Pradesh vide letter No.1168/Hg-II/2017 dated 12.02.2019.
xvii	Occupational health surveillance of the workers be done on a regular basis and records maintaned as per the factories Act.	Complied 1) Occupational health centre has been set up in the premises of the factory. 2) We have engaged part-time doctor and paramedical staff. 3) The occupational health surveillance of the workers is being carried-out on regular basis and the records are being maintained as per Factories Act.
B.GEN	ERAL CONDITIONS	
j.	The project authorities Shall strictily adhere to the stipulations made by the Andra pradesh state pollution Control Board.	-
ii.	At no time, the emissions shall exceed the prescrided limits. In the event of failure of any pollution Control system adopted	Agreed to comply
	by the unit shall be immediately put out of operation and shall not be restarted until the desired efficiency has been achieved.	

		has been achieved.
III,	No further expansion or modifions in the plant shall be carried out without prior approval of the Ministry of Environment and Forests. In case of deviations or alterations in the project proposal from those submitted to this Ministry for clearance, a fresh reference shall be made to the Ministry to assess the adequacy of conditions imposed and to add additional envirinmental protection measures required, if any	Complied No expansion or modifications were carried out without the approval of the Ministry. Now we are going for expansion from 142.32 TPA to 500 TPA and the application is submitted to Ministry.
iv.	The project authorities shall strictly comply with the rules and regulations under Manufature, Storage and import of Hazardous Chemicals Rules, 1989 as amended in October, 1994 and january, 2000. Authorization from the the SPCB shall be obtained for collection, treatmentt, storage, disposal of hazardous wastes.	a) We have obtained Authorization from APPCB to handle Hazardous Waste as per notification and we are implementing the stipulation. b) It is informed that all the solid wastes generated in the form of process waste including organic residue and spent carbon is collected, stored and being sent to TSDF for secured land fil also given to the authorized cement industries. Sludge from ETP and evaporation salts are being sent to TSDF for landfill. Used oil and mixed solvents is being sent to authorized recyclers/cement plants. Containers and container liners of hazardous chemicals are being sent to Recyclers after complete detoxification. c) The Hazardous waste Authorization is valid up to 31.03.2021.
V.	The project authorities must strictly comply with the rules and regulations with regard to handling and disposal of hazardous wastes in accordance with the Hazardousd Wastes (Management ,handling and Transboundary Movement) Rules ,2008 , Authorization from the state pollution Control Boards must be obtanied for collection/ treatment/ storage/ disposal of hazardous wastes.	Complied a) It was submitted that the condition is noted and assured to abide by the condition.

operation immediately and will not be restarted until the desired efficiency

		b)	It is informed that the solid waste and hazardous waste are being sent to the SPSCB authorised parties only.
		c)	Regularly obtaining renewal of consent and authorization from SPCB and is valid up-to 31.03.2021.
vi	The overall noise levels in and around the plant area shall be kept well within the standards (85dBA) by providing noise control measure including acoustic hoods, Silencers, enclosures etc. on all sources of noise generation. The ambient noise levels shall conform to the standards prescribed under Environment Protection Act, 1986 rules, 1989 viz 75 dBA (day time) and 75 dBA (night time)	a)	Complied The ambient noise levels in and around the plant area is being monitored at 6 locations (Near Boiler, Near Security Gate Near Chilling Plant, Near Production, Near DG set and Near ETP) both day and night through authorized third party and the values are well within the limits.
		b)	Data on ambient noise levels is being regularly submitted to the RO, MoEF &CC, Chennai. The monitored data shows that the values are well within the limits.
		c)	Noise controlling measures such as silencers and acoustic hoods are provided for DG sets.
vii	The project proponent shall also comply with all the environmental protection measures and safe guards recommended in the Environment Impact Assessment Notification, 1994 report	Repor protec	Reportedly complied tedly complied environmental tion measures and safeguards ommended in EIA report.
viii	A seperate Environmental Management Cell equipped with full pledged laboratory facilities shall be setup to carry out Environmental Management and Monitoring functions	A Manag with q	Complied separate Environmental gement Cell has been set up qualified officers. Laboratory is ed with full-fledged facilities equipment for monitoring

		Chemical Oxygen Demand (COD), Dissolved Oxygen (DO), Biological Oxygen Demand (BOD), Conductivity, TDS and pH. Effluent quality is also monitoring in addition to third party. AAQ and stack emission are monitored through external agency in addition to online monitoring facilities. Noise levels are also monitored through external approved lab.
ix	The project authorities shall enmark separate funds to implement the conditions stipulated by the MoEF as well as State Government along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.	Complied It is to inform that an amount of Rs.384.0 lakhs and Rs.79.5 lakhs towards capital cost and recurring cost/annum for environment pollution control measures were allotted and spent. The fund provided / allotted was not diverted for any other purpose as informed.
X	The implementation of the project vis-a-vis environmental action plans shall be monitored by Ministry's regional office at Banglore/SPCB/Central Pollution Control Board. A six monthly compliance status report shall be submitted to monitoring agencies.	-
хi	The project proponent shall inform the public that the project has been accorded environmental clearance by the ministry and copies of the clearance letter are available with the SPCB/Committee and may also be seen at website of the ministry at http://envifor.nic.in . This shall be advertised with seven days from the date of issue of the clearance letter, at least in two local news papers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and copy of the same shall be forwarded to the Ministry's Regional Office at Banglore.	We had given advertisement both in English (Deccan Chronical) on 23.08.2009 and Telugu (Sakshi) on 22.08.2009 in local news paper and provided copy of the same to RO,
xii	The project authorities shall inform the Regional office as well as Ministry,the date of financial closure and final approval of the project by the concerned authorities and date of start of the project.	











